

**MATERIAL SAFETY DATA SHEET**

Revised 08/15/03

**SECTION I – PRODUCT IDENTIFICATION**

Manufacturer: Lenderink & Associates  
1267 House St. NE  
Belmont, MI 49306

Phone: 616-887-8257  
Fax: 616-887-7910  
www.lenderink.com

Trade Name: Dribond #506 (.024")  
C.A.S. Number: N/A  
D.O.T. Hazard Class: N/A  
Proper Shipping Name: N/A  
Technical Name: N/A

! Hazard Ratings: Health – 1  
! none → extreme Fire – 1  
! 0 → 4 Reactivity – 0

Personal Protection – none

**SECTION II – HAZARDOUS INGREDIENTS**

Ingredients	CAS#	Weight %	Exposure Limits		VP mmHG
			ACGIH/TLV	OSHA/PEL	
NONE	MIXTURE	100%	N/A	N/A	

**SECTION III – PHYSICAL DATA**

Boiling Range: N/A

Vapor Rate: N/A

Appearance: Elastomeric sheets, films, tubing and profiles,  
Various Colors

Vapor Density: N/A

Liquid Density: N/A

Spec. Gravity: >1.0

**SECTION IV – FIRE AND EXPLOSION HAZARD DANGER**

Flash Point (D1929-CC): greater than 390 degrees C (740 degrees F) Flammable Limits: LEL: N/A UEL: N/A

- EXTINGUISHING MEDIA

Water, ABC dry chemicals, protein air foam

- SPECIAL FIREFIGHTING PROCEDURES

Wear NIOSH approved self-contained breathing apparatus by trained personnel.

- UNUSUAL FIRE & EXPLOSION HAZARDS

These polymers are combustible when forced to burn and may emit toxic odors.

**Lenderink & Associates**  
**Material Safety Data Sheet for: Dribond #506 (.024")**  
**Revised 08/15/03**

---

**SECTION V – HEALTH HAZARD DATA**

---

- PERMISSIBLE EXPOSURE LEVEL: See Section II.
- PRIMARY ROUTES OF EXPOSURE: are processing vapors by inhalation; neither skin nor ingestion are known to be routes of exposure
- EFFECTS OF OVEREXPOSURE  
ACUTE: heat processing at or above the decomposition point may release the products discussed in Section Six including the isocyanate MDI which may result in irritation of the respiratory tract and eyes, chest tightness, coughing, headache, and dyspnea. Sensitization with subsequent asthma-like attacks may follow.

CHRONIC:

Carcinogenicity: NTP?: No IARC Monographs?: No OSHA Regulated?: No

Signs and Symptoms of Exposure: processing vapors above the melting point may cause irritation of respiratory tract, eyes, and skin; processing temperatures at or above the decomposition point may release products including MDI which may cause irritation of the respiratory tract, eyes, skin, chest tightness, coughing, headache, and dyspnea.

Medical Conditions Generally Aggravated by Exposure: none known

Emergency and First Aid Procedures:

- INHALATION: of vapors, remove to fresh air. If breathing has stopped, restore breathing and get medical attention.
- SKIN CONTACT: if hot molten polyurethane contacts skin, flush immediately with water and seek medical attention for thermal burn.
- EYE CONTACT: Flush with water for at least 15 minutes. If irritation develops or persists consult a physician.

---

**SECTION VI – REACTIVITY DATA**

---

STABILITY: [ ] Unstable [ X ] Stable

HAZARDOUS POLYMERIZATION: [ ] May occur [ X ] Will not occur

- INCOMPATIBILITY:  
None known
- CONDITIONS TO AVOID:  
None known but avoid heating to temperatures above 250 degrees C.
- SPECIFIC HAZARDS:  
Carbon monoxide, carbon dioxide, oxides of nitrogen, hydrogen cyanide, aliphatic and aromatic hydrocarbons, including MDI (methylene bisphenyl isocyanate) may be created during incomplete combustion.

**Lenderink & Associates**  
**Material Safety Data Sheet for: Dribond #506 (.24")**  
**Revised 08/15/03**

---

**SECTION VII – SPILL OR LEAK PROCEDURES**

---

- STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED  
Sweep up and place in properly marked container.
- WASTE DISPOSAL METHOD  
Dispose of in accordance with all local, state and federal regulations.
- Other Precautions:  
None known

---

**SECTION VIII – SPECIAL PROTECTION INFORMATION**

---

- RESPIRATORY PROTECTION  
For processing above the melting point, NIOSH approved, supplied air respirators should be used not required for normal ambient use.
- VENTILATION  
Local Exhaust: when melt processing to remove vapors exhaust hoods should maintain a minimum of 100 fpm face velocity.
- PROTECTIVE GLOVES  
Recommended when handling hot product
- EYE PROTECTION  
Safety glasses or face shield
- OTHER PROTECTIVE EQUIPMENT  
Use impermeable clothing whenever possible to prevent skin contact
- Work/HYGENIC PRATICES  
Maintain good personal hygiene as standard good work practice

---

**SECTION IX – REGULATORY INFORMATION**

---

- SARA TITLE III SECTION 313  
Not applicable based on article exemption
- PROPOSITION 65  
WARNING: SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER: None
- PROPOSITION 65  
WARING: SUBSTANCES KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM: None

---

**SECTION X – DISCLAIMER**

---

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of Lenderink Technologies. The data on this sheet relates only to the specific material designated herein. Lenderink Technologies assumes no legal responsibility for use or reliance upon these data.

---